

Innovet Select Specifications

Integrated 60 Hz Generator

- kVp range: 40 - 125, 64 selections
- mA stations: 100S, 300L
- Timer range: 1/120th - 1 second, 18 selections
- mAs range: .8 - 300 mAs
- Digital mAs readout
- Digital kVp readout
- Digital diagnostic readout
- Tilt-out control panel
- Built-in tube protection circuits
- Adjustable volume, audible exposure signal
- Automatic generator "Shut Off" circuit*
- SCR contactor
- UL classified

Table / Tubestand

- Enclosed, integrated radiographic table
- Table top: 53 in. x 24 in.
- Welded base construction
- Transformer mounting shelf*
- Grid cabinet with Simplex™ cassette tray*
- Grid: 8:1 ratio, 103 LPI
- Grid cabinet / tubestand interlock
- Animal restraining device*
- Angulation dial and deluxe operator handgrips*
- Tubestand handles*
- UL classified

X-Ray Tube C458

- 1.0 - 2.0 mm F.S., 140,000 heat units

Cables C600-10

- 10 ft. high voltage cables with federal terminations

Collimator G800

- Manual collimator with light field
- Swivel mount*
- Field light "on" time - selectable 30, 60, 90 or 120 seconds
- Long life "soft-start" bulb circuits
- Spare collimator bulb*
- Easy-to-operate with gloves on
- Exceeds federal standards for radiation leakage protection for medical systems

Exposure Switch A981

- Foot switch with 20 ft. cord

Generator Options

- Additional mA station, specify 30 mA or 400 mA
- High Frequency (HF) generator, 30KW, 300mA, 125kVp, in lieu of 60 Hz generator
 - Anatomical programmed console tube-mounted
 - 500 mA generator upgrade, including step-up transformer
 - (Eight mA stations: 50S, 100S, 200L, 300L, 350L, 400L, 450L, 500L)
 - 500 mA and anatomical programmed console together
 - Step-up transformer L246 for line voltages measuring 200 - 229 VAC
 - Exposure foot treadle with latching prep circuit K241 in lieu of foot switch
 - Wall mounted, remote hand operated exposure switch W413 in lieu of foot switch

Table / Tray Options

- Two-way float-top table, 58 in. x 32 in. with +/- 4 in. transverse travel
- Four-way float-top table, 67 in. x 32 in. with +/- 4 in. transverse and longitudinal travel
- Extended length for float-top table, 67 in.
- Stationary table top extension, 12 in., specify left or right, W414
- Standard manual cassette tray B144 in lieu of Simplex™ tray
- Cassette storage bin and accessory drawer, specify left, right or both (price per bin), K827
- Table-top fluid trough

Tube / Collimator Options

- "No-hands" collimator light system, K262
- Upgrade tube to 0.6 - 1.5 mm F.S., 200,000 heat units, E411